

MİNİ PLAKALI CHİLLER PERFORMANS CETVELİ

KAPASİTE DEĞERLERİ R 404 A GAZINA GÖRE SEÇİLMİŞTİR

CİHAZ TİPİ	KOMPRESÖR	KONDANSASYON	SOĞUTMA KAPASİTESİ (W) EVAPORASYON(°C)									ELEKTRİKSEL VERİLER		
			-20	-15	-10	-5	0	5	10	15	WATT	VOLT	AKIM	
MPC 12	4450/0,5	40°C	514	637	794	982	1197	1436	1693	1962	629	220/50	3,87 A	
		45°C	460	571	714	885	1081	1298	1531	1773				
		50°C	-	506	634	788	965	1159	1367	1582				
MPC 34	9480/0,75	40°C	891	1135	1414	1728	2079	2466	2887	3334	955	220/50	4,55 A	
		45°C	786	1011	1266	1553	1874	2227	2610	3016				
		50°C	685	889	1120	1380	1670	1989	2334	2699				
MPC 100	9510/1	40°C	1119	1407	1747	2133	2559	3018	3501	3997	1198	220/50	5,90 A	
		45°C	998	1261	1572	1924	2312	2728	3164	3609				
		50°C	876	1114	1396	1714	2063	2437	2826	3220				
MPC 110	9513/1,1	40°C	1229	1636	2100	2624	3209	3854	4554	5300	1448	220/50	7,20 A	
		45°C	1073	1447	1871	2350	2884	3471	4108	4785				
		50°C	930	1269	1654	2086	2568	3096	3671	4278				
MPC 130	4517/1,3	40°C	1600	2000	2487	3053	3688	4380	5117	5880	1623	220/50	7,90 A	
		45°C	1432	1794	2238	2753	3331	3960	4626	5312				
		50°C	-	1588	1987	2451	2971	3536	4132	4742				
MPC 150	4519/1,5	40°C	2016	2604	3279	4034	4856	5733	6649	7582	2202	220/50	10,50 A	
		45°C	1804	2336	2951	3638	4386	5182	6011	6851				
		50°C	-	2067	2620	3239	3912	4628	5369	6116				
MPC 200	4524/2	40°C	1944	2644	3437	4338	5364	6532	7858	9358	2327	220/50	11,30 A	
		45°C	1649	2306	3042	3872	4813	5883	7096	8470				
		50°C	-	1964	2639	3395	4249	5216	6313	7557				
MPC 250	4531/2,5	40°C	2456	3517	4590	5716	6937	8292	9823	11570	3024	220/50	16,40 A	
		45°C	1927	2992	4042	5119	6264	7517	8918	10510				
		50°C	-	2449	3477	4505	5573	6724	7997	9433				